

K115D Hydraulic Computerized Cutting Machine



K-L series, with high-resolution 15" touch colorful LCD from CHIMEI INNOLUX, extremely robust and sensitive touch screen considerably improves operator convenience. Easy operation to active all functions via touch screen, Simple programming, even of complex cutting functions, through full graphic representation as well as animation display of the entire cutting process(all working steps) for easy operational control, almost infinite storage for program. Remote control management and remote diagnosis are configured with the easy-acknowledged keys. Paper feeder adopts Japanese servo motor. The speed can be adjusted steplessly with maximum 30times/min with automatic knife-changing function. The hydraulic system is imported from the famous German company. The pressure of the clamp is adjustable range from 150dan to 7000dan, which totally meet the CE safety standard.

Specifications:

Max. cutting length	1150 mm
Max. cutting width	1150 mm
Max. cutting height	165 mm
Min. cutting	
(without pressure plate)	25 mm
(including pressure plate)	90 mm
Length (cutting point to front table)	735 mm
Length (cutting point to back table)	1605 mm
Height of working platform from ground	900 mm
Additional platform length	650 mm
Additional platform width	750 mm
Platen pressure (min.)	1.5 KN

Platen pressure (max.)	45 KN
Blade specifications	13.75 mm
Sharpening place (max.)	60 mm
Cutting speed	45 t/min